

Product Qualification

--- Compatibility Test ---

Product Name: SFD 25A-M 32GB (ET)

Product P/N: APS25A4B (7)032G-8A (B)TM1G (W)

Firmware Version: SFDG108A (B)

Controller: SCJC72

Qualification: Qual all

Test Result: PASS

APPROVAL					
QT	Date	Signature	Approved by	Date	Signature
Alex Lin	2017/06/30	Alex Lin	Danny Chen	2017/06/30	Danny Chen

Table Of Content

SUMMARY RESULT 3

A. Function Test With M/B : ASUS H97M-E 4

 1. Basic Function Test 4

 2. Format Test..... 4

 3. Burn In Test 4

 4. Reboot Test..... 4

 5. Install System Test..... 4

 6. Test Result 4

B. Function Test With M/B : Avalue EMX QM77-A1R 5

 1. Basic Function Test 5

 2. Install System Test..... 5

 3. Test Result 5

C. Performance Test With M/B : ASUS Z170-A 6

D. Performance Test With M/B : Asus Maximus VI Hero 7

E. Platform Compatibility Test..... 8

F. Additional Qualification: 9

 1. Environmental 9

 2. Certification..... 9

SUMMARY RESULT

		PC1	PC2	PC3	PC4						
Testing Product		SFD 25A-M 32GB									
System		Windows 10	Fedora kernel 3.3.4 -5 fc17								
M/B	Name	H97M-E	QM77-A1R								
	Vendor	ASUS	Avalue EMX								
	Chipset	Intel H97	Intel QM77								
	Interface	SATA III	SATA III								
	BIOS	2602	V1.1.0								
Test Result											
Basic Function Test		V	V								
Burn In Test	Comp32	V	--								
	PassMark Burn In Test Pro V8.0	V	--								
	PassMark Burn In Test Pro V3.0.1007	--	--								
Warm Boot Test		V	--								
Cold Boot Test		V	--								
		--	--								
		--	--								
Install System Test											
	Windows Emb. 7 Standard	Windows Emb. 8 Standard	Windows Emb. 8.1 Industry	Windows 10	Fedora kernel 3.3.4 -5 fc17	Ubuntu kernel 3.13.0 -32	Red Hat kernel 2.6.32 -431.e16				
Result	V	V	V	V	V	V	V				
Remark:						Test Result — PASS					

A. Function Test With M/B : ASUS H97M-E

Testing Product	SFD 25A-M 32GB	Testing Engineer	Alex Lin
Testing Environment	M/B: ASUS H97M-E	Chipset: Intel H97 Interface: SATA III	BIOS: 2602

1. Basic Function Test

	Copy	Delete	Restart	Compare	Suspend (S3)	Hibernate (S4)	LED
Windows 10	V	V	V	V	V	V	V

2. Format Test

	FAT32	NTFS
Windows 10	29.7GB	29.8GB

3. Burn In Test

	Comp32 15 hours	Burn In Test V8.0 Pro 168 hours
Windows 10	V	V

4. Reboot Test

	Warm Boot 6000 Cycles	Cold Boot 6000 Cycles
Windows 10	V	V

5. Install System Test

Install System	Result
Install Windows Embedded Standard 7 System	V
Install Windows Embedded 8 Standard System	V
Install Windows Embedded 8.1 Industry Pro System	V
Windows 10 Multiple Edition	V
Windows 10 Enterprise	V

6. Test Result

Pass

B. Function Test With M/B : Avalue EMX QM77-A1R

Testing Product	SFD 25A-M 32GB	Testing Engineer	Alex Lin
Testing Environment	M/B: Avalue EMX QM77-A1R	Chipset: Intel QM77 Interface: SATA III	BIOS: V1.1.0

1. Basic Function Test

	Copy	Delete	Restart	Compare	Suspend (S3)	Hibernate (S4)	LED
Fedora kernel 3.3.4 -5 fc17	V	V	V	V	V	V	V

2. Install System Test

Install System	Result
Install Windows Embedded Standard 7 System	V
Install Windows Embedded 8 Standard System	V
Install Windows Embedded 8.1 Industry Pro System	V
Install Windows 7 System	V
Install Windows 8.1 System	V
Install Fedora kernel 3.3.4 -5 System	V
Install Ubuntu kernel 3.13.0 -32 System	V
Install Red Hat Kernel 2.6.32 -431.e16 System	V

3. Test Result

Pass


C. Performance Test With M/B : ASUS Z170-A

Testing Product	SFD 25A-M 32GB	Testing Engineer	Alex Lin
Testing Environment	M/B: ASUS Z170-A	Chipset: Intel Z170 Interface: SATA III	BIOS: 1302
Testing Software	CrystalMark 3.0.2		

Test Function : BurnIn Test 168hrs				
Before		After		
4K Q16T1	179.7	102.3	181.4	102.0
Seq	385.9	102.6	385.6	102.3
4K	30.96	56.18	30.84	60.66

D. Performance Test With M/B : Asus Maximus VI Hero

Testing Product	SFD 25A-M 32GB	Testing Engineer	Alex Lin
Testing Environment	M/B: ASUS Maximus VI Hero	Chipset: Intel Z87 Interface: SATA III	BIOS: 0224
Testing Software	Ubuntu 14.10 Benchmark		



E. Platform Compatibility Test

Platform	Chipset	M/B	Interface	System	Result
PC1	Intel Z68	Asus P8Z68-M Pro	SATA III	Win8.1	V
PC2	Intel Z77	Gigabyte IVB	SATA III	Win8.1	V
PC3	Intel Z87	Asus Maximus VI Hero	SATA III	Win8.1	V
PC4	Intel Z77	GA-Z77X-D3H	SATA III	Win8.1	V
PC5	Intel QM77	Avalue EMX QM77-A1R	SATA III	Win8.1	V
PC6	AMD 790FX	Asus M4A79T Deluxe	SATA III	Win8.1	V
PC7	AMD 790GX	Asus M4A78T-E	SATA III	Win8.1	V
PC8	AMD A88X	Asus A88XM-A	SATA III	Win8.1	V

Apacer

F. Additional Qualification:

1. Environmental

- 1. RoHS Standard 2011/65/EU , 2015/863/EU
- 2. Other Environmental Standard EC/1907/2006
- 3. WEEE (By Product) 2012/19/EU
- 4. Battery Standard N/A
- 5. Packing Standard 94/62/EC
- 6. Others N/A

2. Certification

- 1. CE No. _____
- 2. FCC No. _____
- 3. BSMI No. _____
- 4. VCCC No. _____
- 5. C-tick No. _____
- 6. Other _____

